



### Main benefits

#### **High resolution**

0.1 mm resolution for accurate measurements.

#### Free of parallax error

Its exclusive screen-lens system avoids missing the ends of the haloes through its unique perpendicular reading technology.

#### **Digital display**

Results are clearly featured in a digital display.

#### **Plate verification**

A standard set of disks (10, 20 & 30 mm Ø) allows to verify the device.



#### Product Overview

Making a precise inhibition zone measurement manually can be challenging. The Haloes Caliper helps to perform this in a simple and precise way while avoiding parallax errors in readings.


A precision rotating wheel accurately measures the inhibition zones while being manually spun. This comes in handy in antibiotic susceptibility testing and antibiotic potency measurements.



### Workflow



Place the Petri Dish in the Haloes Caliper's illuminated field.



Place one side of the halo on the calibration line and push the reset button.



Move the wheel to the opposite side of the halo.



Observe the result on the digital display.

#### Verification disks



## Technical specifications

Magnification	Factor 2.25
Measuring range	0–35 mm
Resolution	0.1 mm
Mains	100/240V 50/60Hz
Power	15W
Dimensions (W×D×H)	27×23×27 cm / 10.6×9.0×10.6 in
Weight	3 kg / 6.6 lb

Specifications subject to change without notice.

### Accessories and spare parts

- 1. Diameter verification disks (10, 20 & 30 mm) Cat. 9000919
- Pattern for 6 halos (10 units)Cat. 90002131
- **3.** Pattern for 4 halos (10 units) **Cat. 90002132**
- 4. Millimiter grid Cat. 9000985

# Ordering information

 Haloes Caliper - Inhibition zone reader unit Cat. 9000900





For more information about Haloes Caliper, scan the QR code

For more information visit us at:

www.iul-instruments.com

IUL SA Carrer de la Ciutat d'Asunción, 4 - 08030 Barcelona (Spain) sales@iul-inst.com • T. +34 93 274 02 32



