Main benefits

No Sample Cross Contamination

Samples are protected from any contamination during homogenization thanks to the use of sterile disposable bags.

Robust

Second to none in endurance, the Masticator's high quality spring system has proven to withstand the most challenging blending procedures.

Easy of use

The Masticators are easily cleaned when fully removing their front door.

Wide application scope

Choose the model that fits your needs. Compatible with 80, 400, or 3500 ml bags.



Product Overview

The Masticator is a laboratory paddle blender that carries out a profund homogenization in order to obtain a representative sample for food, cosmetics, pharmaceutical, and clinical quality control, while isolating them from any possible contamination.

The Masticator's high-quality and durable motor ensure safe and efficient homogenization. The Masticator homogenizes samples inside sterile bags thanks to its paddles that drive a masticating action while moving the sample from side to side. This key step in sample preparation ensures an homogenous distribution of microorganisms throughout the diluent. Several models encompass a wide array of possibilities.



Paddle blender bags: strenght, endurance, sterilized

The bags are sterilized with irradiation ensuring no risk of cross-contamination. They hold three features that represent IUL's product quality: strength, endurance, and sterilization.

The side of the bags are perfectly sealed, without soiling or contaminating any part of the sample. These bags are manufactured from extruded polymer tubes using high-grade, food quality polythene. This brings unrivaled strength and endurance. IUL is ISO 9001 certified to quality management system standards, guaranteeing IUL quality performance.











_	
COM	pact
COII	pace

80 ml bags* 100 mm x 150 mm 3.93 in x 5.90 in (WxH) 65 mµ (thk.)

*from 20 to 80 ml samples

Classic/Panoramic **Basic/Panoramic**

400 IIII bags"
180 mm x 300 mm 7.08 in x 11.81 in (WxH)
65 mμ (thk.)

*from 80 to 400 ml samples

Silver/Panoramic

400 ml bags with filter* 165 x 260 mm 6.49 in x 10.23 in (WxH) 60 mµ (thk.)

*from 80 to 400 ml samples

MAXICATOR

3500 ml bags*
380 mm x 500 mm 14.96 in x 19.68 in (WxH)
65 mμ (thk.)

*from 400 to 3500 ml samples

Accessories and consumables












80 ml bags

- 1. 2000 units (50 by 50) Cat. 90002456
- **2.** 6000 units (50 by 50) Cat. 90002457
- 400 ml bags 1. 500 units (50 by 50) Cat. 900014050
- 2. 5000 units (50 by 50) Cat. 90005421
- 400 ml bags with filter
- 1. 500 units (25 by 25) Cat. 900014501
- 2. 2000 units (25 by 25) Cat. 90002451
- 3. 5000 units (25 by 25) Cat. 90002452
- 3500 ml bags
- 1. 250 units (50 by 50) Cat. 900014035





1. Stand and tray for any 400 ml Masticator Cat. 9000742

2. Stainless steel holder for six 400 ml bags

Cat. 90002300



3. Stainless steel holder for six 80 ml bags Cat. 90002380





4. Plastic tray Cat. 9000743 (Masticator) Cat. 900011524 (Maxicator)



■ Wide range for different uses









▼ Workflow



Introduce the sample into the sterile bag.



Close the door leaving the top of the bag visible.



Set the parameters (timer, and strokes/second), and start the process closing the door.



Pick up the bag with the homogenized sample ready to be analyzed.

How to automate the whole process



Smart Dilutor W - Gravimetric Dilutor

Get a full processing capacity and traceability in gravimetric dilutions or liquid dispensing.



Eddy Jet 2W – Spiral plater

Eddy Jet 2W spiral plater is used to reduce the number of plates processed, offering a threefold decimal dilution counting range in a single plate.



Technical specifications











രവ	m	bags
ou		uaes

00 ml bags	400 ml bags

400 ml bags

3500 ml bags

Model	Compact	Basic/Panoramic	Classic/Panoramic	Silver/ Panoramic	MAXICATOR
Strokes/sec	10	8.5 (50Hz) 10 (60Hz)	8.5 (50Hz) 10 (60Hz)	5-6-7-8	3-4-5-6
Setting	Digital Timer	Digital Timer	Digital Timer	Keyboard/Display	Keyboard/Display
Timer	15/30/60/90s	15/30/60/90s	15/30/60/90s	15/30/60/90/120/ 150/180/210/240s	15/30/60/90/120/ 150/180/210/240s
Paddles & door	Stainless steel	Stainless steel	Stainless steel	Stainless steel	Stainless steel
Inner part	Stainless steel	Steel	Stainless steel	Stainless steel	Stainless steel
Dimensions (WxHxD)	15x15x30 cm 5.9x5x11.8 in	24x26x40 cm 9.4x10.2x15.7 in	24x26x40 cm 9.4x10.2x15.7 in	24x26x40 cm 9.4x10.2x15.7 in	44x50x57 cm 17.3x19.7x22.4 in
Weight	7 kg / 15.4 lb	17 kg / 37.5 lb	17 kg / 37.5 lb	20 kg / 44 lb	52.5 kg / 116 lb
No. of Paddles	2	2	2	2	4

Specifications subject to change without notice.

Order information

- 1. Masticator Basic 400 ml. a. Cat. 9000470 (220/240 V) b. Cat. 9000471 (100/127 V)
- 2 Masticator Basic Panoramic 400 ml. a. Cat. 9000475 (220/240 V)
 - b. Cat. 9000477 (100/127 V)
- 3. Masticator Classic 400 ml.
 - **a. Cat. 9000400** (220/240 V)
 - **b. Cat. 9000401** (100/127 V)
- **4.** Masticator Classic Panoramic 400 ml. **a. Cat. 9000500** (220/240 V)
 - **b.Cat. 9000501**(100/127 V)
- 5. Masticator Silver 400 ml.
 - **a.Cat. 9000420** (220/230 V)
 - **b.Cat. 9000421** (100 V)
 - **c. Cat. 9000461** (100/120 V)
- 6. Masticator Silver Panoramic 400 ml.
 - a.Cat. 9000520 (220/230 V)
 - **b.Cat. 9000521** (100 V)
 - **c. Cat. 9000522** (100/120 V)

- 7. Masticator Compact 80 ml.
 - **a. Cat. 900085** (220/230 V)
 - **b. Cat. 900086** (100 V) **c. Cat. 900087** (100/120 V)
- 8. MAXICATOR 3500 ml.
 - a. Cat. 90002400 (220/230 V)
 - **b. Cat. 90002401** (100 V)







For more information about Masticator, scan the QR code

For more information visit us at:

www.iul-instruments.com

IUL SA Carrer de la Ciutat d'Asunción, 4 - 08030 Barcelona (Spain) sales@iul-inst.com • T. +34 93 274 02 32



