

STERIDIUM

# 1200L Cooled Co2 Incubator

Model iCo2r1200



# 1200L Cooled Co2 Incubator

## Model iCo2r1200

### Product Specifications

Chamber Capacity	1200L
Chamber Dimensions	700 x 600 x 1240 mm (w d h) per side
External Dimensions	1900 x 855 x 1915 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	4 to 50C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1 C
Spatial Stability	+/- 2C
Shelf Positions	26 (13 per side)
Shelves Supplied	6 ( 3 per side)
Shelf Support Spacing	78
Insulation Type	Mineral wool
Insulation Thickness	50 mm
Co2 Range	2-20 %
Optional range on request	0-3000 PPM
Co2 Connection	4mm Hose Barb



**Brisbane, Australia**

+61 7 55 931 352

sales@steridium.com

steridium.com



# 1200L Cooled Co2 Incubator

## Model iCo2r1200

### Product Specifications

Electrical Supply	Single phase, 220-240V, 50Hz (alternatives available on request)
Electrical Connection Rating	15 Amps
Circulating fans	2 - Base mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia



STERIDIUM

# 1200L Cooled Co2 Incubator

## Model iCo2r1200

### Options / Accessories

- Additional Shelf
- Single Chamber Configuration
- Inner Viewing Door - Tempered Glass
- Double Glazed Door
- Castors
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- ISPM15 Compliant Export Crating
- Heating Only - See model i1200
- Standard Co2 Incubator - See model iCo2-1200



**Brisbane, Australia**

+61 7 55 931 352

[sales@steridium.com](mailto:sales@steridium.com)

[steridium.com](http://steridium.com)

