

STERIDIUM

160L Peltier Cooled Co2 Incubator Model iCo2-160



160L Peltier Cooled Co2 Incubator

Model iCo2-160

Product Specifications

Chamber Capacity	160L
Chamber Dimensions	515 x 520 x 586 mm (w d h)
External Dimensions	658 x 727 x 857 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	(ambient+7) to 50C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1C
Spatial Stability	+/- 1C
Shelf Positions	5
Shelves Supplied	2
Shelf Support Spacing	89 mm
Insulation Type	Mineral wool
Insulation Thickness	50 mm
Co2 Range	2-20 %
Optional range on request	0-3000 PPM
Co2 Connection	4mm Hose Barb



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com



160L Peltier Cooled Co2 Incubator

Model iCo2-160

Product Specifications

Electrical Supply	Single phase, 220-240V, 50Hz (alternatives available on request)
Electrical Connection Rating	10 Amps
Circulating fans	1 - Rear mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia




STERIDIUM

160L Peltier Cooled Co2 Incubator

Model iCo2-160

Options / Accessories

- Additional Shelf
- Inner Viewing Door - Perspex
- Double Glazed Door
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- Enhanced RH - Reduced drying out of samples
- ISPM15 Compliant Export Crating
- Heating only - See model ico2-160



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com

