

STERIDIUM

170L Freestanding Oven

Model of170



170L Freestanding Oven

Model of170

Product Specifications

Chamber Capacity	170L
Chamber Dimensions	700 x 600 x 406 mm (w d h)
External Dimensions	882 x 793 x 955 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	(ambient+7) to 200C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1 C
Spatial Stability	+/- 2C
Shelf Positions	4
Shelves Supplied	2
Shelf Support Spacing	73
Insulation Type	Mineral wool
Insulation Thickness	50 mm



170L Freestanding Oven

Model of170

Product Specifications

Electrical Supply	Single phase, 220-240V, 50Hz (alternatives available on request)
Electrical Connection Rating	10 Amps
Circulating fans	1 - Base mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia



170L Freestanding Oven

Model of170

Options / Accessories

- Additional Shelf
- Castors
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- ISPM15 Compliant Export Crating
- Drying of moisture laden content - see model dg170
- Soil Drying - see model ds170

