

STERIDIUM

810L Co2 Incubator

Model ico2-810



810L Co2 Incubator

Model ico2-810

Product Specifications

| | |
|---------------------------|-----------------------------------|
| Chamber Capacity | 810L |
| Chamber Dimensions | 842 x 705 x 1373 mm (w d h) |
| External Dimensions | 1048 x 881 x 1982 mm (w d h) |
| Chamber Material | Stainless Steel (304 L) |
| External Material | Durable epoxy powder-coated steel |
| Temperature Range | (ambient+7) to 80C |
| Temperature Sensor | pt100 |
| Temporal Stability | +/- 0.1 C |
| Spatial Stability | +/- 2C |
| Shelf Positions | 16 |
| Shelves Supplied | 3 |
| Shelf Support Spacing | 77 |
| Insulation Type | Mineral wool |
| Insulation Thickness | 50 mm |
| Co2 Range | 2-20% |
| Optional range on request | 0-3000 PPM |
| Co2 Connection | 4mm Hose Barb |



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com



810L Co2 Incubator

Model ico2-810

Product Specifications

| | |
|------------------------------|---|
| Electrical Supply | Three phase, 380-41V, 50Hz (alternatives available on request) |
| Electrical Connection Rating | 16 Amps / Phase |
| Circulating fans | 1 - Base mounted |
| Countdown Timer | Included |
| Controller Type | Intelligent PID - microprocessor |
| Readout | Digital LCD |
| Place of manufacture | Brisbane, Australia |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |
| | |



Brisbane, Australia
 +61 7 55 931 352
 sales@steridium.com
 steridium.com



810L Co2 Incubator

Model ico2-810

Options / Accessories

- Additional Shelf
- Inner viewing door - Tempered Glass
- Double Glazed Door
- Castors
- Enhanced RH - Reduced drying out of samples
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- ISPM15 Compliant Export Crating



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com