

STERIDIUM

810L Refrigerated Incubator

Model ir810



810L Refrigerated Incubator

Model ir810

Product Specifications

Chamber Capacity	810L
Chamber Dimensions	842 x 705 x 1373 mm (w d h)
External Dimensions	1048 x 881 x 1982 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	4 to 60C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1 C
Spatial Stability	+/- 2C
Shelf Positions	16
Shelves Supplied	3
Shelf Support Spacing	77
Insulation Type	Mineral wool
Insulation Thickness	50 mm



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com



810L Refrigerated Incubator

Model ir810

Product Specifications

Electrical Supply	Three phase, 380-41V, 50Hz (alternatives available on request)
Electrical Connection Rating	16 Amps / Phase
Circulating fans	1 - Base mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia



810L Refrigerated Incubator

Model ir810

Options / Accessories

- Additional Shelf
- Inner viewing door - Tempered Glass
- Double Glazed Door
- Castors
- Enhanced RH - Reduced drying out of samples
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- ISPM15 Compliant Export Crating



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com