

STERIDIU M

1620L Freestanding Oven

Model of 1620



1620L Freestanding Oven

Model of1620

Product Specifications

Chamber Capacity	1620L
Chamber Dimensions	700 x 600 x 1780 mm (w d h)
External Dimensions	1900 x 855 x 2455 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	(ambient+7) to 200C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1 C
Spatial Stability	+/- 2C
Shelf Positions	38 (19 per side)
Shelves Supplied	8 (4 per side)
Shelf Support Spacing	78
Insulation Type	Mineral wool
Insulation Thickness	50 mm



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com



1620L Freestanding Oven

Model of 1620

Product Specifications

Electrical Supply	Three phase, 380-41V, 50Hz (alternatives available on request)
Electrical Connection Rating	20 Amps / Phase
Circulating fans	2 - Base mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia



1620L Freestanding Oven

Model of 1620

Options / Accessories

- Additional Shelf
- Castors
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- ISPM15 Compliant Export Crating
- Drying of moisture laden content - see model dg1620
- Soil Drying - see model ds1620

