

STERIDIUM

30L Laboratory Incubator

Model i30



30L Laboratory Incubator

Model i30

Product Specifications

Chamber Capacity	30L
Chamber Dimensions	263 x 302 x 360 mm (w d h)
External Dimensions	406 x 521 x 632 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	(ambient+7) to 80C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1 C
Spatial Stability	+/- 1C
Shelf Positions	3
Shelves Supplied	2
Shelf Support Spacing	79 mm
Insulation Type	Mineral wool
Insulation Thickness	50 mm



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com



30L Laboratory Incubator

Model i30

Product Specifications

Electrical Supply	Single phase, 220-240V, 50Hz (alternatives available on request)
Electrical Connection Rating	10 Amps
Circulating fans	1 - Rear mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia



STERIDIUM

30L Laboratory Incubator

Model i30

Options / Accessories

- Additional Shelf
- Inner Viewing Door - Perspex
- Double Glazed Door
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- Enhanced RH - Reduced drying out of samples
- ISPM15 Compliant Export Crating
- Co2 Control - See model ico2-30
- Cooling below ambient - See model ip-30



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com

