

STERIDIUM

320L Laboratory Incubator

Model i320



320L Laboratory Incubator

Model i320

Product Specifications

Chamber Capacity	320L
Chamber Dimensions	700 x 600 x 755 mm (w d h)
External Dimensions	882 x 793 x 1305 mm (w d h)
Chamber Material	Stainless Steel (304 L)
External Material	Durable epoxy powder-coated steel
Temperature Range	(ambient+7) to 80C
Temperature Sensor	pt100
Temporal Stability	+/- 0.1 C
Spatial Stability	+/- 2C
Shelf Positions	8
Shelves Supplied	2
Shelf Support Spacing	75
Insulation Type	Mineral wool
Insulation Thickness	50 mm



320L Laboratory Incubator

Model i320

Product Specifications

Electrical Supply	Single phase, 220-240V, 50Hz (alternatives available on request)
Electrical Connection Rating	10 Amps
Circulating fans	1 - Base mounted
Countdown Timer	Included
Controller Type	Intelligent PID - microprocessor
Readout	Digital LCD
Place of manufacture	Brisbane, Australia




320L Laboratory Incubator

Model i320

Options / Accessories

- Additional Shelf
- Inner Viewing Door - Tempered Glass
- Double Glazed Doors
- Castors
- Side Access Port - 50 mm
- Calibration Certificate
- 8 Step Programmable Controller - 4 Ramp/Dwell Pairs
- ISPM15 Compliant Export Crating
- Co2 Control - See model ico2-320
- Cooling below ambient - See model ir-320



Brisbane, Australia

+61 7 55 931 352

sales@steridium.com

steridium.com